



PM500-118 (FS/3) Universal Optical Probe



Features

- Compatible with virtually all utility meters, registers and recorders that employ ANSI C12.18-1996 and GE OPTOCOM communications protocols
- Designed for use with ITRON FS/3 handheld
- Rugged design with aluminum housing
- Molded cable construction with high-end endurance polyurethane
- Powerful retention magnets for attaching to meter's optical port
- Power to probe controlled by Meter Reading Software
- Operates over a wide range of temperature (-30° C TO +65° C)
- Polycarbonate filter to enhance infrared (IR) communications

Overview

The **PM500-118** Optical Probe is designed for reading and programming electric power meters employing the ANSI Type 2 optical port. Its optical circuitry supports ANSI C12.18-1996 and General Electric OPTOCOM communications protocols by switching automatically from one to the other depending on the meter type being read. It can also be configured to read and program through IEC 61107 FLAG-compliant meters. This probe is specifically configured for use with the Itron FS/3 handheld computers.

The PM500-118 utility meter reading probe uses advanced optical sensors to collect meter data and transmit it to the Itron hand-held computer. This allows metering data to be recorded more simply, accurately and efficiently. In addition, the PM500-118 incorporates a universal compatibility design to read virtually all utility meters, registers and recorders.

Mechanical Specifications

Physical Size	Height 2.44"; Length 1.68"; Width 1.38"
Cable Type	Coiled, Polyurethane & Hytrel construction, Flexible & Rugged
Cable Length	18" Coiled, extends to 10'
Connector	Amphenol, 12-pin, male, gold-plated contacts
Weight	Complete assembly weighs a max. of 9oz.
Finish	Probe head has a clear anodized outer coating per MIL-A-63576A, Type I

Electrical Specifications

Signal Spec	TTL, Hand-held Serial port
Power Req.	Operating Supply Voltage: 4.5 to 6.0 VDC (from Computer's host port). Power to probe controlled by meter reading software.
Data Rate	Controlled by meter for OPTOCOM interface, 0 to 19,200 baud for Non-OPTOCOM meters
Optical	880 nm bi-directional IR interface, ANSI C12.18 1996, GE OPTOCOM

Environmental Specifications

Temperature	Operating -30° to 60° C; Storage -40° to +85° C
Ruggedness	Meets the requirements of a number of tests including those for Thermal Shock, Humidity, Water Resistance, RF Susceptibility, ESD, Drop, Random Vibration, Solar Radiation, Salt, Fog & Low Pressure

Compatible Meters

ABB	2550, 2650, All Alpha, Alpha T, A3, Alt, Alr-al, 2430
Aptech/Robinton	LPR1, LPR2, LPR3, SR500, TR403, TR804
General Electric	DR87, KM901, M90-AE, Phase 3, T80, T91, TM80, TM81, TMR82, TM92, KC901, KTC-901, KV, KV2, KV2-C
Siemens (Landis&Gyr)	CTR101, CTR102, DC, DCR, DD, DG100, DT, DX, DXR, SD100, SM101, SM301, TMC101, LINC, DCRMA, DDMA, S4 family, AX series, RX series, MAXSYS 2410, MAXSYS 2510, Quad 4
Metricom	C
PSI	S100, S200, Quad 4
Pwr Measurement	ION 7000 series, 8000 series
Itron (Schlumberger)	Datastar, Fulcrum, MT100, MT200, Quantum, Q1000, Sentinel, Centron, Vectron
Synergistics	B40
Transdata	EMA, Mark V

Corporate Office:

uData Net Corp.
6320 Southwest Blvd., Ste. 205
Fort Worth, Texas 76109
(817) 348-9700 Tele
(817) 348-9701 Facsimile
www.udatanet.com

Manufacturing Office:

uData Net Corp.
3247 N. 38th Street
McAllen, Texas 78501
(956) 631-5300 Tele
(956) 631-5193 Facsimile
www.udatanet.com